

Safety Data Sheet
Malic acid



Revision 7

01/12/2014 - EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

(*)1.1. Product identifier

Commercial name: **Malic acid**
REACH registration number: 01-2119906954-31-0000
Index number: NOT AVAILABLE
International Chemical Identification: Malic acid
CAS number: 6915-15-7
EC number: 230-022-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Industrial use:

Intermediates, mixtures and formulated, pH-regulating agents.

Professional use:

Mixtures and formulated, pH-regulating agents, fertilizers, metal surface treatment products, non - metal surface treatment products, flocculant agents, precipitants, neutralization agents, disincrustants, Washing and cleaning products, cosmetics, personal care products, water softeners, water treatment chemicals, Laboratory chemicals.

Consumers use:

Food/feed additives, Cosmetic products, personal care products, Water softeners, Disinfectant, Washing and cleaning products, disincrustant solutions for hemodialysis equipment,

1.3. Details of the supplier of the safety data sheet

Producer: Polynt S.p.A.
Via Enrico Fermi 51
24020 Scanzorosciate (BG)
ITALY
Telephone number: +39 035 652 111
msds@polynt.com

Supplier: Polynt S.p.A.
Via Enrico Fermi 51
24020 Scanzorosciate (BG)
ITALY
Telephone number: +39 035 652 111

1.4. Emergency telephone number

+39 035 652 276

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Reg CE 1272/2008

Hazard statement Code(s)

Serious eye damage/eye irritation
H319: Causes serious eye irritation.

Hazard Class and Category Code(s)

Eye Irrit. 2

Reg CE 548/1967 o Reg CE 45/1999

Xi - Irritant; R36 - Irritating to eyes.

2.2. Label elements

Labelling according to Regulation 1272/2008/EC.

Contains: Malic acid
INDEX N° Not available

Safety Data Sheet
Malic acid



Revision 7

01/12/2014 - EN

CAS N° 6915-15-7

EC N° 230-022-8

Pictograms:



WARNING

Hazard statement:

H319: Causes serious eye irritation.

Precautionary statements:

P264: Wash eyes thoroughly after handling.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P280: Wear protective gloves/eye protection/face protection. (see MSDS).

P337+P313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No other Known

SECTION 3: Composition/information on ingredients

(*)3.1. Substances

Malic acid

International Chemical Identification: Malic acid

Index No: NOT AVAILABLE

Chemical formula: C4H6O5

Concentration range: >= 99,0 %

Registration number: 01-2119906954-31-0000

CAS No: 6915-15-7

EC No: 230-022-8

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Skin:

After contact with skin, wash immediately with plenty of soap and water. Consult a physician.

Eye:

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Call a physician immediately.

Ingestion:

Call a physician immediately. Clean mouth with water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Safety Data Sheet
Malic acid



Revision 7

01/12/2014 - EN

Irritating to eyes and skin.

4.3. Indication of any immediate medical attention and special treatment needed

See section 4.1.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Appropriate fire-fighting equipment:

Foam, powder, water spray.

Inappropriate fire-fighting equipment

Do not use water jets as they can disperse and spread fire.

5.2. Special hazards arising from the substance or mixture

In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Water mist may be used to cool closed containers.

Use personal protective equipment to protect skin/eyes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Move any people not authorised to contain the emergency out of the area.

Avoid coming in contact with the substance or handling containers without adequate protection.

Use the personal protective equipment described in section 8.

Use a respirator in the event of emissions/spillage of large quantities.

Eliminate all sources of ignition.

Remove all incompatible materials as outlined in section 10.5 of SDS.

Avoid dust formation.

6.2. Environmental precautions

Contain the spillage as far as possible.

Prevent spilled materials getting into the drainage system, wells, surface water or groundwater.

In the case of leaks into a water course, drains, or if the product has contaminated the ground or vegetation, contact the local authorities.

6.3. Methods and material for containment and cleaning up

Do not use equipment that can generate sources of ignition when cleaning. Clean the spilled material mechanically and put it in an appropriate container for disposal in accordance with section 13. After collection, ventilate and clean the affected area with water before granting access. Do not flush the water used for cleaning into watercourses or down drains.

6.4. Reference to other sections

See sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Recommendations for safe use:

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid contact with skin and eyes.

Avoid accumulation of electrostatic charges, to prevent risk of powders exploding.

Avoid formation of respirable particles.

Revision 7

01/12/2014 - EN

Advice on general occupational hygiene:

Do not eat, drink or smoke when using this product.
Wash face and hands thoroughly after handling.
Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Eliminate all sources of combustion.
Keep container hermetically closed in a dry and well ventilated environment.
Avoid the formation of dust.
Keep away from incompatible materials (see point 10.5).
Keep away from food, feed and beverages.

7.3. Specific end use(s)

None identified.

SECTION 8: Exposure controls/personal protection

(*)8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL) / DERIVED MINIMUM EFFECT LEVEL (DMEL) :

Workers:

Short-term systemic effects:

Inhalation: DNEL: 8,8 mg/m³ Assessment factor 50
Dermal: DNEL: 40 mg/kg bw/day Assessment factor 50

Long-term systemic effects:

Inhalation: DNEL: 10,6 mg/m³ Assessment factor 50
Dermal: DNEL: 12 mg/kg bw/day Assessment factor 50

General population:

Short-term systemic effects:

Oral: DNEL 20 mg/kg bw/day Assessment factor 100
Inhalation: DNEL 2,2 mg/m³ Assessment factor 100
Dermal: DNEL 20 mg/kg bw/day Assessment factor 100

Long-term systemic effects:

Oral: DNEL 6 mg/kg bw/day Assessment factor 100
Inhalation: DNEL 2,6 mg/m³ Assessment factor 100
Dermal: DNEL 6 mg/kg bw/day Assessment factor 100

PREDICTED NO EFFECT CONCENTRATION (PNEC) :

Environment:

Water:

PNEC water (freshwater): 0.1 mg/L Assessment factor 1000
PNEC water (marine water): 0.01 mg/L Assessment factor 10000
PNEC water (intermittent releases): 1 mg/L Assessment factor 100

Soil:

PNEC soil: 0.275 mg/kg soil dw

Sediment:

PNEC sediment (freshwater): 0.275 mg/kg sediment dw
PNEC sediment (marine water): 0.027 mg/kg sediment dw

STP:

PNEC STP: 3 mg/L Assessment factor 100

Revision 7

01/12/2014 - EN

Occupational Exposure limit values:

National: Undetermined

European: Undetermined

8.2. Exposure controls

Appropriate engineering controls:

See annexe of this file.

Eye / face protection:

Goggles or protective visor.

Skin protection / of the Hand:

The material the gloves are made of must be impermeable and stable when in contact with the substance. No specific information available on the suitability of the material and thickness of the gloves. Consult the glove manufacturer for specific information on the suitability of the gloves. Replace the gloves in the case of internal contamination, when punctured, or if external contamination cannot be removed. The actual duration of protection depends on the conditions of use.

Skin protection / of the body:

Use suitable protective clothing for chemical substances.

Respiratory protection:

Mask with P3 dust filter if solid or type A filter for vapours and organic gases with a boiling point > 65°C if molten. (EN 149)

Environmental exposure controls:

See annexe of this file.

SECTION 9: Physical and chemical properties

(*9.1. Information on basic physical and chemical properties

a1) **Appearance:** Solid crystalline powder

a2) **Color:** White

b) **Odour:** Characteristics

c) **Odour threshold:** NOT AVAILABLE

d) **pH:** NOT AVAILABLE

e1) **Melting point:** 131 °C @ 1013 hPa

f1) **Initial boiling point:** NOT APPLICABLE

g) **Flash point:** NOT AVAILABLE

h) **Evaporation rate:** NOT APPLICABLE

i) **Flammability (solid, gas):** Not flammable

j1) **Upper flammability limits:** NOT AVAILABLE

j2) **Lower flammability limits:** NOT AVAILABLE

Revision 7

01/12/2014 - EN

- j3) Upper explosive limits: NOT AVAILABLE
- j4) Lower explosive limits: 187.5 g/m³
- k) Vapour pressure: 0.00039 Pa @ 25°C
- l) Vapour density: NOT AVAILABLE
- m) Relative density: 1.615 @ 20°C
- n) Water solubility: 647 g/l @ 20°C
- o) Partition coefficient: n-octanol/water: -1.26 @ 25°C
- p) Auto-ignition temperature: NOT AVAILABLE
- q) Decomposition temperature: NOT AVAILABLE
- r) Viscosity: NOT APPLICABLE
- s) Explosive properties: NOT EXPLOSIVE
- t) Oxidising properties: NOT OXIDIZING

9.2. Other information

Not any.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known in normal conditions.

10.4. Conditions to avoid

Avoid the build-up of electrostatic charges.
Avoid exposure to heat sources.
Avoid the formation of dust.

10.5. Incompatible materials

Oxidizing agents, alkalis, alkali metals, amines and carbonates.
Unsuitable container materials: iron, zinc, aluminium. Aqueous solutions of Malic Acid can release explosive hydrogen gas if in contact with these active metals.

10.6. Hazardous decomposition products

Unknown

Revision 7

01/12/2014 - EN

SECTION 11: Toxicological information

(*)11.1. Information on toxicological effects

Acute toxicity:

Oral:

Method:

equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
rat (Wistar) male/female oral: gavage

Results:

LD50: 3500 mg/kg bw based on: test mat.

Inhalation:

Method:

Read-across from supporting substance (structural analogue or surrogate)
OECD Guideline 403 (Acute Inhalation Toxicity)
EU Method B.2 (Acute Toxicity (Inhalation))
rat (Sprague-Dawley) male/female, Inhalation: dust (nose only)

Results:

LC50 (4h): 1306 mg/m³ air based on: test mat.

Dermal:

Method:

Read-across from supporting substance (structural analogue or surrogate)
Others. Rabbit (New Zealand White) Coverage: occlusive.

Results:

LD50: 20000 mg/kg bw

Conclusions: not classified

Skin corrosion/irritation:

Method:

Read-across from supporting substance (structural analogue or surrogate)
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Rabbit (small white Russian); Coverage: occlusive (shaved)

Results:

Slightly irritating

Serious eye damage/eye irritation:

Method:

Read-across from supporting substance (structural analogue or surrogate)
OECD Guideline 405 (Acute Eye Irritation / Corrosion) Rabbit (small white Russian)

Results:

Irritating Category 2

Respiratory or skin sensitisation:

Respiratory Sensitisation: Not available

Skin Sensitisation:

Method:

Read-across from supporting substance (structural analogue or surrogate)
OECD Guideline 406 (Skin Sensitisation) guinea pig (Dunkin-Hartley) female,
Induction: intradermal and epicutaneous.

Results:

Not sensitising

Germ cell mutagenicity:

In vitro:

Bacterial reverse mutation assay (e.g. Ames test) (gene mutation).

Method:

equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
S. typhimurium TA 1535, TA 1537, TA 98 and TA 100, S. typhimurium, other:
TA 92 and TA 94. (met. act.: with and without).

Results: negative.

Revision 7

01/12/2014 - EN

Mammalian cell gene mutation assay (gene mutation).

Method:

OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test).
mouse lymphoma L5178Y cells. (met. act.: with and without).

Results: negative.

Mammalian chromosome aberration test (chromosome aberration):

Method:

equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test). Chinese hamster lung fibroblasts (V79) (met. act.: without)

Results: negative.

Carcinogenicity: not available

Reproductive toxicity:

Effects on sexual function and fertility:

Oral:

Method:

equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); rat male/female, Oral: feed.

Results:

NOAEL (P): 10000 ppm (male/female) based on: test mat.

LOAEL (F2): 10000 ppm (male/female) based on: test mat.

Effects on development of the offspring:

Oral:

Method:

equivalent or similar to OECD Guideline 414 (Prenatal Developmental Toxicity Study)
rat (Wistar). Orale: gavage.

Results:

NOEL (maternal toxicity): 350 mg/kg bw/day

NOEL (developmental toxicity): 350 mg/kg bw/day

Conclusions: not classified

Specific target organ toxicity (STOT) - Single exposure:

not available

Specific target organ toxicity (STOT) - Repeated exposure:

Oral:

Method:

equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
rat male/female, chronic (oral: feed), Exposure: 104 weeks (Continuous (in feed))

Results:

NOEL: 5000 ppm (male/female) based on: test mat.

LOEL: 50000 ppm (male/female) based on: test mat.

Value used for CSA: NOAEL: 600 mg/kg bw/day

Conclusions: not classified

Aspiration hazard: not available

SECTION 12: Ecological information

(*)12.1. Toxicity

Toxicity to aquatic environment:

Short-term toxicity to the aquatic environment:

Fish:

Method:

OECD Guideline 203 (Fish, Acute Toxicity Test)
Danio rerio; freshwater; semi-static

Results:

LC50 (96 h): > 100 mg/L test mat. (nominal)

NOEC: 100 mg/L

Revision 7

01/12/2014 - EN

Aquatic invertebrates:

Method:

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Daphnia sp. freshwater; static.

Results:

LC50 (48h): 240 mg/L test mat. based on: mortality
EC50: 240 mg/L

Algae or other aquatic plants:

Method:

Read-across from supporting substance (structural analogue or surrogate)
OECD Guideline 201 (Alga, Growth Inhibition Test)
Pseudokirchnerella subcapitata (algae); freshwater; static.

Results:

EC50 (72 h): > 100 mg/L test mat. (nominal) based on: biomass
EC50 (72 h): > 100 mg/L test mat. (nominal) based on: growth rate
NOEC (72 h): 100 mg/L test mat. (nominal) based on: biomass
NOEC (72 h): 100 mg/L test mat. (nominal) based on: growth rate
Value used for CSA: EC10/LC10 or NOEC: 100 mg/L

Aquatic microorganisms:

Method:

Read-across from supporting substance (structural analogue or surrogate)
OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
activated sludge of a predominantly domestic sewage; freshwater; static

Results:

EC50 (3 h): > 300 mg/L test mat. (nominal) based on: respiration rate

Long-term toxicity to aquatic environmental: not available

Toxicity to the Terrestrial environment: not available

(*)12.2. Persistence and degradability

Degradability:

Abiotic degradation: not available

Biotic degradation:

Aquatic environment:

Method:

OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Test type: ready biodegradability, activated sludge (adaptation not specified)

Results:

readily biodegradable
% Degradation of test substance:
73% after 14 d (O₂ consumption) (BOD)
99% after 14 d (TOC removal) (TOC)
100% after 14 d (Test mat. analysis) (HPLC)

Value used for CSA: Readily biodegradable

(*)12.3. Bioaccumulative potential

Bioaccumulation:

Log Pow: 1,26

Aquatic environment:

Method:

Weight of evidence. ECHA Guidance on information requirements and chemical safety assessment - Chapter R.06: QSARs and grouping of chemicals - May 2008

Results:

BCF: 1 L/kg (whole body w.w.)

Value used for CSA: BCF: 1 L/kg ww (L/kg ww or dimensionless)

Terrestrial environment: Data not available

Safety Data Sheet
Malic acid



Revision 7

01/12/2014 - EN

Conclusions: These data indicate that the substance is not bioaccumulative (B).

(*)12.4. Mobility in soil

Adsorption/desorption:

In accordance with REACH Regulation 1907/2006, Annex VIII - 9.3.1 Column 2, screening tests for adsorption/desorption do not need to be conducted as the substance has a low potential for adsorption based on a log Kow of - 1.26

Volatilisation:

Method:

Others: Weight of evidence

Results:

Henry's Law constant: 0.000000086 Pa m³/mol at 25 °C

Distribution among environmental compartments:

Method:

Weight of evidence. Calculation programme: EPI Suite (v.4.10).

Calculation according to Mackay, Level III

Media: air - biota - sediment(s) - soil - water;

Results:

Percent distribution in media:

Air (%): 0,0001

Water (%): 26,4

Soil (%): 73,6

Sediment (%): 0,0344

12.5. Results of PBT and vPvB assessment

Substance is not Persistent (P) (see section 12.2)

Substance is not bioaccumulative (B) (see section 12.3)

Substance is not classified toxic (T)

Conclusions:

Based on available information, the substance is not PBT vPvB.

12.6. Other adverse effects

No other known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recycle if possible, or send to an authorized incinerator. Follow the instructions in sections 6 and 7 when handling waste spillages, taking the steps indicated in the same sections. We recommend recycling containers instead of disposal. Observe the local and national legislation in force.

SECTION 14: Transport information

14.1. UN number

NOT APPLICABLE

14.2. UN proper shipping name

NOT APPLICABLE

14.3. Transport hazard class(es)

NOT APPLICABLE

14.4. Packing group

NOT APPLICABLE

14.5. Environmental hazards

Safety Data Sheet
Malic acid



Revision 7

01/12/2014 - EN

NOT APPLICABLE

14.6. Special precautions for user

NOT APPLICABLE

ADR/RID

- Tunnel restriction code: NOT APPLICABLE
- Category - limited quantities per transport unit: NOT APPLICABLE
- LQ code - limited quantities per pack unit: NOT APPLICABLE
- E code excepted quantities: NOT APPLICABLE

IMDG

- LQ code - limited quantities per pack unit: NOT APPLICABLE
- E code excepted quantities: NOT APPLICABLE
- Ems: NOT APPLICABLE

ICAO/IATA

- Packing Instructions / max. net quantities per package per plane - combi and cargo: NOT APPLICABLE
- Packing Instructions / max. net quantities per package in limited quantity regime: NOT APPLICABLE
- EQ code for excepted quantities regime: NOT APPLICABLE

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Regulation 1907/2006/EC (Reach)
European Regulation 1272/2008/EC (CLP)
European Regulation 453/2010/EU
DIRECTIVE 548/1967/EEC;
DIRECTIVE 45/1999/EC;
DIRECTIVE 24/1998/EC;
DIRECTIVE 37/2004/EC;
DIRECTIVE 92/1999/EC;
DIRECTIVE 82/1996/EC;

(*15.2. Chemical safety assessment

CSR/CSA: yes

SECTION 16: Other information

Safety Data Sheet compiled according to Regulation 453/2010/EU.

Exposure Scenarios in local languages will be published as soon as they are available.

(* on the left indicate the modifications with respect to the last version.

References:

GESTIS International Limit Values.

Acronyms:

ACGIH: American Conference of Governmental Industrial Hygienist.
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ASTM: American Society of Testing and Materials.
B: Bioaccumulabile.
BCF: BioConcentration Factor.

Safety Data Sheet
Malic acid



Revision 7

01/12/2014 - EN

BSAF: Biological Soil Accumulation Factor.
CSA: Chemical Safety Assessment.
CSR: Chemical Safety Report.
DIN: Deutsches Institut für Normung.
DMEL: Derived Minimal Effect Level.
DNEEL: Derived No Effect Level.
Ec: Effective concentration.
EC50: Effective Concentration 50 (that produces an effect (other than death) for 50% of organisms test).
ECx: Effective Concentration 50 (that produces an effect (other than death) for X% of organisms test).
EPA: Environmental Protection Agency.
IATA: International Air Transport Association.
IBC: International code for the construction and equipment of ships carrying dangerous Bulk Chemicals.
ICAO: International Civil Air-transport Organisation.
IMGD: International Maritime Dangerous Goods code.
ISO: International Standards Organisation.
KoC: organic carbon/water partition coefficient (adsorption coefficient).
KoW: n-octanol/water partition coefficient.
LC50: Lethal Concentration for 50% of animal test.
LCx: Lethal Concentration for X% of animal test.
LD50: Lethal Dose for 50% test animal.
LDx: Lethal Dose for X% test animal.
LLNA: Local Lymph Node Assay.
LOAEC: Lowest Observed Adverse Effect Concentration.
LOAEL: Lowest Observed Adverse Effect Level.
LOEC: Lowest Observed Effect Concentration.
LOEL: Lowest Observed Effect Level.
MARPOL: International Convention for the Prevention of Pollution from Ships.
NOAEC: No Observed Adverse Effects Concentration.
NOAEL: No Observed Adverse Effect Level.
NOEC: No Observed Effect Concentration.
NOEL: No Observed Effect Level.
OECD-OCSE: Organisation for Economic Co-operation and Development.
P: Persistent.
PBT: Persistent Bioaccumulable and Toxic.
PNEC: Predicted No Effect Concentration.
(Q)SAR: Quantitative Structure-Activity Relationship.
RID: Regulations concerning the International carriage of Dangerous goods by rail.
SDS: Safety Data Sheet.
STP: Sewage Treatment Plant.
TLV: Threshold Limit Value.
TLV-C: Threshold Limit Value - Ceiling.
TLV-STEL: Threshold Limit Value - Short Term Exposure Limit.
TLV-TWA: Threshold Limit Value - Time Weighted Average.
vPvB: very Persistent and very Bio-accumulative.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

EXPOSURE SCENARIOS

Table of Contents

1. ES 1: Formulation of preparations1

1.1. Formulation of preparations: Fertilizers/ Metal surface treatment products, including galvanic and electroplating products/ Non-metal-surface treatment products/ Products such as ph-regulators, flocculants, precipitants, neutralization agents/ Perfumes, fragrances/ Washing and cleaning products (including solvent based products)/ Water softeners / Water treatment chemicals..... 1

1.2. Conditions of use affecting exposure	1
1.2.1. Control of environmental exposure: Formulation (ERC 2)	1
1.2.2. Control of worker exposure: Use in closed batch process (PROC 3)	1
1.2.3. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC5)	2
1.2.4. Control of worker exposure: Transfer from/to large non-dedicated facilities (PROC 8a).....	2
1.2.5. Control of worker exposure: Transfer from/to large non-dedicated facilities (PROC 8a).....	2
1.2.6. Control of worker exposure: Transfer from/to large dedicated facilities (PROC8b).....	3
1.2.7. Control of worker exposure: Transfer from/to large dedicated facilities (PROC8b).....	3
1.2.9. Control of worker exposure: Use as laboratory reagent (PROC 15).....	4
1.3. Exposure estimation and reference to its source	4
1.3.1. Environmental release and exposure: Formulation (ERC 2)	4
1.3.2. Worker exposure: Use in closed batch process (PROC 3).....	4
1.3.3. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC 5).....	4
1.3.4. Worker exposure: Transfer from/to large non-dedicated facilities (PROC 8a)	4
1.3.5. Worker exposure: Transfer from/to large non-dedicated facilities scenario (PROC 8a)	4
1.3.6. Worker exposure: Transfer from/to large dedicated facilities (PROC 8b).....	5
1.3.7. Worker exposure: Transfer from/to large dedicated facilities (PROC 8b).....	5
1.3.8. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)	5
1.3.9. Worker exposure: Use as laboratory reagent (PROC 15)	5

2. ES 2: Use at industrial site6

2.1. SU 1: Agriculture, forestry, fishery SU 10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys) SU 15: Manufacture of fabricated metal products, except machinery and equipment SU 16: Manufacture of computer, electronic and optical products, electrical equipment SU 17: General manufacturing SU 19: Building and construction work SU 20: Health services SU 24: Scientific research and development)..... 6

2.2. Conditions of use affecting exposure	6
2.2.1. Control of environmental exposure: Use at industrial site (ERC 4).....	6
2.2.3. Control of worker exposure: Industrial spraying (PROC 7)	7
2.2.4. Control of worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)	7
2.2.5. Control of worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC8b)	7

2.2.7. Control of worker exposure: Use as laboratory reagent (PROC 15)..... 8

2.2.8. Control of worker exposure: Low energy manipulation of substances bound in materials and/or articles (PROC 21) 9

2.3. Exposure estimation and reference to its source 9

2.3.1. Environmental release and exposure: Use at industrial site (ERC 4)..... 9

2.3.2. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC 5)..... 9

2.3.3. Worker exposure: Industrial spraying (PROC 7)..... 9

2.3.4. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a) 9

2.3.5. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC 8b) 10

2.3.6. Worker exposure: Production of preparations or articles by tableting, compression, extrusion, pelletisation (PROC 14) 10

2.3.7. Worker exposure: Use as laboratory reagent (PROC 15) 10

2.3.8. Worker exposure: Low energy manipulation of substances bound in materials and/or articles (PROC 21)..... 10

3. ES 3: Use at industrial site11

3.1. Use as intermediate 11

3.2. Conditions of use affecting exposure 11

3.2.1. Control of environmental exposure: Use at industrial site (ERC 6a)..... 11

3.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC 1) 11

3.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC 2) 12

3.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC 3) ... 12

3.2.5. Control of worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4) 12

3.2.7. Control of worker exposure: Transfer of substance or preparation from/to vessels/large containers at dedicated facilities (PROC8b) 13

3.2.9. Control of worker exposure: Use as laboratory reagent (PROC 15)..... 14

3.3. Exposure estimation and reference to its source 14

3.3.1. Environmental release and exposure: Use at industrial site (ERC 6a) 14

3.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC 1)..... 14

3.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC 2) 14

3.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)..... 14

3.3.5. Worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4) 15

3.3.6. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a) 15

3.3.7. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC 8b) 15

3.3.8. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9) 15

3.3.9. Worker exposure: Use as laboratory reagent (PROC 15) 15

4. ES 4: Use by professional workers16

4.1. Use by professional workers of fertilizers, metal surface treatment products, non - metal surface treatment products, ph-regulators, flocculant agents, precipitants, neutralization agents, disinfectants, Washing and cleaning products, cosmetics, personal care products, water softeners, water treatment

chemicals	16
4.2. Conditions of use affecting exposure	16
4.2.1. Control of environmental exposure (ERC 8a,8b,8d,8e).....	16
4.2.2. Control of worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a).....	16
4.2.3. Control of worker exposure: Transfer of substance or preparation from/to vessels/large containers at dedicated facilities (PROC8b)	17
4.2.4. Control of worker exposure: Roller application or brushing (PROC 10)	17
4.2.5. Control of worker exposure: Non industrial spraying (PROC 11).....	17
4.3. Exposure estimation and reference to its source	18
4.3.1. Environmental release and exposure: Scenario covers also ERC 8a, 8b and 8e (ERC 8d):	18
4.3.2. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)	18
4.3.3. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC 8b)	18
4.3.4. Worker exposure: Roller application or brushing (PROC 10).....	18
4.3.5. Worker exposure: Non industrial spraying (PROC 11)	18
5. ES 5: Use by professional worker	19
5.1. Use in professional laboratories	19
5.2. Conditions of use affecting exposure	19
5.2.1. Control of environmental exposure: Use by professional worker (ERC8a,8b,8c,9a).....	19
5.2.2. Control of worker exposure: use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4)	19
5.2.3. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC5).....	20
5.2.4. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)	20
5.3. Exposure estimation and reference to its source	21
5.3.1. Environmental release and exposure: Use by professional worker (ERC8a,8b,8c,9a)	21
5.3.2. Worker exposure: use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4)	21
5.3.3. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC 5).....	21
5.3.4. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)	21
6. ES 6: Consumer Use	22
6.1. Water softners/ Cosmetics, personal care products/ Disinfectant, disincrustant solutions for hemodialysis equipment/ Washing and cleaning products	22
6.2. Conditions of use affecting exposure	22
6.2.1. Control of environmental exposure: Consumer Use (ERC 8a, 8c, 8f).....	22
6.2.2. Control of consumer exposure: Water softners -1 (PC 36).....	22
6.2.3. Control of consumer exposure: Cosmetics, personal care products (PC 39)	22
6.2.4. Control of consumer exposure: Disinfectant/disincrustant solutions for hemodialysis equipment (PC 35)	22
6.2.5. Control of consumer exposure: Water treatment chemicals (PC 37).....	23
6.2.6. Control of consumer exposure: Water softners - 2 (PC 36).....	23
6.2.7. Control of consumer exposure: Washing and Cleaning Products (PC 35)	23

6.3. Exposure estimation and reference to its source	23
6.3.1. Environmental release and exposure: Consumer Use (ERC 8a,8c,8f)	23
6.3.2. Consumer exposure: Water softners -1 (PC 36)	23
6.3.3. Consumer exposure: Cosmetics, personal care products (PC 39).....	23
6.3.4. Consumer exposure: Disinfectant/disincrustant solutions for hemodialysis equipment (PC 35)....	23
6.3.5. Consumer exposure: Water treatment chemicals (PC 37)	24
6.3.6. Consumer exposure: Water softners - 2 (PC 36)	24
6.3.7. Consumer exposure: Washing and Cleaning Products (PC 35).....	24

1. ES 1: Formulation of preparations

1.1. Formulation of preparations: Fertilizers/ Metal surface treatment products, including galvanic and electroplating products/ Non-metal-surface treatment products/ Products such as ph-regulators, flocculants, precipitants, neutralization agents/ Perfumes, fragrances/ Washing and cleaning products (including solvent based products)/ Water softeners / Water treatment chemicals.

Environment	
CS 1: Formulation	ERC 2
Worker	
CS 2: Use in closed batch process	PROC 3
CS 3: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)	PROC 5
CS 4: Transfer from/to large non-dedicated facilities	PROC 8a
CS 5: Transfer from/to large non-dedicated facilities	PROC 8a
CS 6: Transfer from/to large dedicated facilities	PROC 8b
CS 7: Transfer from/to large dedicated facilities	PROC 8b
CS 8: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC 9
CS 9: Use as laboratory reagent	PROC 15

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Formulation (ERC 2)

Exposure assessment and risk characterization are not required for the environment as no hazard has been identified for the environment. Additionally the substance has no potential to cause toxic effects if accumulated via food chain. Consequently there is no need to perform an assessment for secondary poisoning.

1.2.2. Control of worker exposure: Use in closed batch process (PROC 3)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in closed batch process (synthesis or formulation)
Advanced (industrial) exposure controls assumed.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.
Indoor use

1.2.3. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC5)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

1.2.4. Control of worker exposure: Transfer from/to large non-dedicated facilities (PROC 8a)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Wear a respirator providing a minimum efficiency of 90.0 %; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

1.2.5. Control of worker exposure: Transfer from/to large non-dedicated facilities (PROC 8a)

Product (article) characteristics
Limit the substance content in the product to 5 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

1.2.6. Control of worker exposure: Transfer from/to large dedicated facilities (PROC8b)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in semi-closed process with opportunity for exposure
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

1.2.7. Control of worker exposure: Transfer from/to large dedicated facilities (PROC8b)

Product (article) characteristics
Limit the substance content in the product to 5 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in semi-closed process with opportunity for exposure
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

1.2.8. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a basic standard of general ventilation (1 to 3 air changes per hour) .
Use in semi-closed process with opportunity for exposure
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

1.2.9. Control of worker exposure: Use as laboratory reagent (PROC 15)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a basic standard of general ventilation (1 to 3 air changes per hour) .
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Formulation (ERC 2)

Not applicable

1.3.2. Worker exposure: Use in closed batch process (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.7 mg/m ³ (TRA Worker v3)	0.019
Dermal, systemic, long-term	0.69 mg/kg bw/day (TRA Worker v3)	0.133
Combined routes, systemic, long-term		0.152

1.3.3. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	17.5 mg/m ³ (TRA Worker v3)	0.478
Dermal, systemic, long-term	1.371 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.742

1.3.4. Worker exposure: Transfer from/to large non-dedicated facilities (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	3.5 mg/m ³ (TRA Worker v3)	0.096
Dermal, systemic, long-term	2.742 mg/kg bw/day (TRA Worker v3)	0.527
Combined routes, systemic, long-term		0.623

1.3.5. Worker exposure: Transfer from/to large non-dedicated facilities scenario (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	7 mg/m ³ (TRA Worker v3)	0.191
Dermal, systemic, long-term	0.548 mg/kg bw/day (TRA Worker v3)	0.106
Combined routes, systemic, long-term		0.297

1.3.6. Worker exposure: Transfer from/to large dedicated facilities (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	17.5 mg/m ³ (TRA Worker v3)	0.478
Dermal, systemic, long-term	1.371 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.742

1.3.7. Worker exposure: Transfer from/to large dedicated facilities (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	3.5 mg/m ³ (TRA Worker v3)	0.096
Dermal, systemic, long-term	0.548 mg/kg bw/day (TRA Worker v3)	0.106
Combined routes, systemic, long-term		0.201

1.3.8. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	20 mg/m ³ (TRA Worker v3)	0.546
Dermal, systemic, long-term	1.372 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.81

1.3.9. Worker exposure: Use as laboratory reagent (PROC 15)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	5 mg/m ³ (TRA Worker v3)	0.137
Dermal, systemic, long-term	0.068 mg/kg bw/day (TRA Worker v3)	0.013
Combined routes, systemic, long-term		0.15

2. ES 2: Use at industrial site

2.1. SU 1: Agriculture, forestry, fishery SU 10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys) SU 15: Manufacture of fabricated metal products, except machinery and equipment SU 16: Manufacture of computer, electronic and optical products, electrical equipment SU 17: General manufacturing SU 19: Building and construction work SU 20: Health services SU 24: Scientific research and development)

Environment	
CS 1: Use at industrial site	ERC 4
Worker	
CS 2: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)	PROC 5
CS 3: Industrial spraying	PROC 7
CS 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities	PROC 8a
CS 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities	PROC 8b
CS 6: Production of preparations or articles by tableting, compression, extrusion, pelletisation	PROC 14
CS 7: Use as laboratory reagent	PROC 15
CS 8: Low energy manipulation of substances bound in materials and/or articles	PROC 21

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Use at industrial site (ERC 4)

Not applicable

2.2.2. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC5)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) .
Local exhaust ventilation - efficiency of at least 90.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

2.2.3. Control of worker exposure: Industrial spraying (PROC 7)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) .
Local exhaust ventilation - efficiency of at least 95.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training.; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

2.2.4. Control of worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Wear a respirator providing a minimum efficiency of 90.0 %; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

2.2.5. Control of worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC8b)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in semi-closed process with opportunity for exposure
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.

Other conditions affecting workers exposure

Ensure operation is undertaken outdoors.

Covers use at temperatures below melting point.

2.2.6. Control of worker exposure: Production of preparations or articles by tableting, compression, extrusion, pelletisation (PROC 14)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a basic standard of general ventilation (1 to 3 air changes per hour) .
Local exhaust ventilation - efficiency of at least 90.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

2.2.7. Control of worker exposure: Use as laboratory reagent (PROC 15)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a basic standard of general ventilation (1 to 3 air changes per hour) .
Local exhaust ventilation - efficiency of at least 90.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

2.2.8. Control of worker exposure: Low energy manipulation of substances bound in materials and/or articles (PROC 21)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a basic standard of general ventilation (1 to 3 air changes per hour) .
Local exhaust ventilation - efficiency of at least 90.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Use at industrial site (ERC 4)

Not applicable

2.3.2. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	1.75 mg/m ³ (TRA Worker v3)	0.048
Dermal, systemic, long-term	2.742 mg/kg bw/day (TRA Worker v3)	0.527
Combined routes, systemic, long-term		0.575

2.3.3. Worker exposure: Industrial spraying (PROC 7)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	3.5 mg/m ³ (TRA Worker v3)	0.096
Dermal, systemic, long-term	4.286 mg/kg bw/day (TRA Worker v3)	0.824
Combined routes, systemic, long-term		0.92

2.3.4. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	3.5 mg/m ³ (TRA Worker v3)	0.096
Dermal, systemic, long-term	2.742 mg/kg bw/day (TRA Worker v3)	0.527
Combined routes, systemic, long-term		0.623

2.3.5. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	17.5 mg/m ³ (TRA Worker v3)	0.478
Dermal, systemic, long-term	1.371 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.742

2.3.6. Worker exposure: Production of preparations or articles by tableting, compression, extrusion, pelletisation (PROC 14)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	1 mg/m ³ (TRA Worker v3)	0.027
Dermal, systemic, long-term	0.686 mg/kg bw/day (TRA Worker v3)	0.132
Combined routes, systemic, long-term		0.159

2.3.7. Worker exposure: Use as laboratory reagent (PROC 15)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.5 mg/m ³ (TRA Worker v3)	0.014
Dermal, systemic, long-term	0.068 mg/kg bw/day (TRA Worker v3)	0.013
Combined routes, systemic, long-term		0.027

2.3.8. Worker exposure: Low energy manipulation of substances bound in materials and/or articles (PROC 21)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	1 mg/m ³ (TRA Worker v3)	0.027
Dermal, systemic, long-term	0.566 mg/kg bw/day (TRA Worker v3)	0.109
Combined routes, systemic, long-term		0.136

3. ES 3: Use at industrial site

3.1. Use as intermediate

Manufacture of fine chemicals (SU 9)	
Environment	
CS 1: Use at industrial site	ERC 6a
Worker	
CS 2: Use in closed process, no likelihood of exposure	PROC 1
CS 3: Use in closed, continuous process with occasional controlled exposure	PROC 2
CS 4: Use in closed batch process (synthesis or formulation)	PROC 3
CS 5: Use in batch and other process (synthesis) where opportunity for exposure arises	PROC 4
CS 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities	PROC 8a
CS 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities	PROC 8b
CS 8: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC 9
CS 9: Use as laboratory reagent	PROC 15

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Use at industrial site (ERC 6a)

Not applicable

3.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC 1)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in closed process, no likelihood of exposure
Advanced (industrial) exposure controls assumed.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.
Indoor use

3.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC 2)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in closed, continuous process with occasional controlled exposure
Advanced (industrial) exposure controls assumed.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.
Indoor use

3.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC 3)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in closed batch process (synthesis or formulation)
Advanced (industrial) exposure controls assumed.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.
Indoor use

3.2.5. Control of worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) .
Use in semi-closed process with opportunity for exposure
Local exhaust ventilation - efficiency of at least 90.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

3.2.6. Control of worker exposure: Transfer of substance or preparation from/to vessels/large containers at non-dedicated facilities (PROC 8a)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.
Wear a respirator providing a minimum efficiency of 90.0 %; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

3.2.7. Control of worker exposure: Transfer of substance or preparation from/to vessels/large containers at dedicated facilities (PROC8b)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in semi-closed process with opportunity for exposure
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at temperatures below melting point.

3.2.8. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in semi-closed process with opportunity for exposure
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.

Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at ambient temperatures.

3.2.9. Control of worker exposure: Use as laboratory reagent (PROC 15)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a basic standard of general ventilation (1 to 3 air changes per hour) .
Local exhaust ventilation - efficiency of at least 90.0 %
Advanced (industrial) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Use at industrial site (ERC 6a)

Not applicable

3.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.007 mg/m ³ (TRA Worker v3)	< 0.01
Dermal, systemic, long-term	0.034 mg/kg bw/day (TRA Worker v3)	< 0.01
Combined routes, systemic, long-term		< 0.01

3.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.7 mg/m ³ (TRA Worker v3)	0.019
Dermal, systemic, long-term	1.37 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.283

3.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.7 mg/m ³ (TRA Worker v3)	0.019
Dermal, systemic, long-term	0.69 mg/kg bw/day (TRA Worker v3)	0.133
Combined routes, systemic, long-term		0.152

3.3.5. Worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	1.75 mg/m ³ (TRA Worker v3)	0.048
Dermal, systemic, long-term	1.372 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.312

3.3.6. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	3.5 mg/m ³ (TRA Worker v3)	0.096
Dermal, systemic, long-term	1.371 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.359

3.3.7. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	17.5 mg/m ³ (TRA Worker v3)	0.478
Dermal, systemic, long-term	1.371 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.742

3.3.8. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	14 mg/m ³ (TRA Worker v3)	0.382
Dermal, systemic, long-term	1.372 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.646

3.3.9. Worker exposure: Use as laboratory reagent (PROC 15)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.5 mg/m ³ (TRA Worker v3)	0.014
Dermal, systemic, long-term	0.068 mg/kg bw/day (TRA Worker v3)	0.013
Combined routes, systemic, long-term		0.027

4. ES 4: Use by professional workers

4.1. Use by professional workers of fertilizers, metal surface treatment products, non - metal surface treatment products, ph-regulators, flocculant agents, precipitants, neutralization agents, disincrustants, Washing and cleaning products, cosmetics, personal care products, water softeners, water treatment chemicals

<ul style="list-style-type: none"> •SU 1: Agriculture, forestry, fishery •SU 15: Manufacture of fabricated metal products, except machinery and equipment •SU 17: General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment. •SU 18: Manufacture of furniture •SU 19: Building and construction work 	
Environment	
CS 1:	ERC 8a,8b,8d,8e
Worker	
CS 2: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities	PROC 8a
CS 3: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities	PROC 8b
CS 4: Roller application or brushing	PROC 10
CS 5: Non industrial spraying	PROC 11

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure (ERC 8a,8b,8d,8e)

Not applicable

4.2.2. Control of worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)

Product (article) characteristics
Limit the substance content in the product to 5 %.
Covers solid products only.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at ambient temperatures.

4.2.3. Control of worker exposure: Transfer of substance or preparation from/to vessels/large containers at dedicated facilities (PROC8b)

Product (article) characteristics
Limit the substance content in the product to 5 %.
Covers solid products only.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Use in semi-closed process with opportunity for exposure
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at ambient temperatures.

4.2.4. Control of worker exposure: Roller application or brushing (PROC 10)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Covers solid products only.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at ambient temperatures.

4.2.5. Control of worker exposure: Non industrial spraying (PROC 11)

Product (article) characteristics
Limit the substance content in the product to 5 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; For further specification, refer to section 8 of the SDS.
Wear a respirator providing a minimum efficiency of 90.0 %; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Ensure operation is undertaken outdoors.
Covers use at ambient temperatures.

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Scenario covers also ERC 8a, 8b and 8e (ERC 8d):

Not applicable

4.3.2. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	7 mg/m ³ (TRA Worker v3)	0.191
Dermal, systemic, long-term	0.548 mg/kg bw/day (TRA Worker v3)	0.106
Combined routes, systemic, long-term		0.297

4.3.3. Worker exposure: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	7 mg/m ³ (TRA Worker v3)	0.191
Dermal, systemic, long-term	0.548 mg/kg bw/day (TRA Worker v3)	0.106
Combined routes, systemic, long-term		0.297

4.3.4. Worker exposure: Roller application or brushing (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	7 mg/m ³ (TRA Worker v3)	0.191
Dermal, systemic, long-term	2.743 mg/kg bw/day (TRA Worker v3)	0.528
Combined routes, systemic, long-term		0.719

4.3.5. Worker exposure: Non industrial spraying (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	2.8 mg/m ³ (TRA Worker v3)	0.076
Dermal, systemic, long-term	2.143 mg/kg bw/day (TRA Worker v3)	0.412
Combined routes, systemic, long-term		0.489

5. ES 5: Use by professional worker

5.1. Use in professional laboratories

<ul style="list-style-type: none"> •SU 9: Manufacture of fine chemicals •SU 20: Health services •SU 24: Scientific research and development 	
Environment	
CS 1: Use by professional worker	ERC 8a, 8b,8c.9a
Worker	
CS 2: use in batch and other process (synthesis) where opportunity for exposure arises	PROC 4
CS 3: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)	PROC 5
CS 4: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC 9

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Use by professional worker (ERC8a,8b,8c,9a)
Not applicable

5.2.2. Control of worker exposure: use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) .
Use in semi-closed process with opportunity for exposure
Local exhaust ventilation - efficiency of at least 80.0 %
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

5.2.3. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC5)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) .
Local exhaust ventilation - efficiency of at least 80.0 %
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at temperatures below melting point.

5.2.4. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers daily exposures up to 8 hours.
Technical and organisational conditions and measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) .
Use in semi-closed process with opportunity for exposure
Local exhaust ventilation - efficiency of at least 80.0 %
Basic (professional) exposure controls assumed.
Conditions and measures related to personal protection, hygiene and health evaluation
Wear suitable gloves tested to EN374.
Other conditions affecting workers exposure
Indoor use
Covers use at ambient temperatures.

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Use by professional worker (ERC8a,8b,8c,9a)

Not applicable

5.3.2. Worker exposure: use in batch and other process (synthesis) where opportunity for exposure arises (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	7 mg/m ³ (TRA Worker v3)	0.191
Dermal, systemic, long-term	1.372 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.455

5.3.3. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	7 mg/m ³ (TRA Worker v3)	0.191
Dermal, systemic, long-term	2.742 mg/kg bw/day (TRA Worker v3)	0.527
Combined routes, systemic, long-term		0.719

5.3.4. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	2.8 mg/m ³ (TRA Worker v3)	0.076
Dermal, systemic, long-term	1.372 mg/kg bw/day (TRA Worker v3)	0.264
Combined routes, systemic, long-term		0.34

6. ES 6: Consumer Use

6.1. Water softeners/ Cosmetics, personal care products/ Disinfectant, disinfectant solutions for hemodialysis equipment/ Washing and cleaning products

Environment	
CS 1: Consumer Use	ERC 8a, 8c, 8f
Consumer	
CS 2: Consumer contributing scenario: Water softeners - 1	PC 36
CS 3: Consumer contributing scenario: Cosmetics, personal care products	PC 39
CS 4: Consumer contributing scenario Disinfectant/disinfectant solutions for hemodialysis equipment	PC 35
CS 5: Consumer contributing scenario: Water treatment chemicals	PC 37
CS 6: Consumer contributing scenario: Water softeners - 2	PC 36
CS 7: Consumer contributing scenario: Washing and Cleaning Products	PC 35

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Consumer Use (ERC 8a, 8c, 8f)

Not applicable

6.2.2. Control of consumer exposure: Water softeners -1 (PC 36)

Amount used, frequency and duration of use/exposure
Covers use up to 300.0 g/event
Frequency: 1 time/day
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to upper part of the body.
Dermal transfer factor: = 1
Contact rate: = 150 mg/min

6.2.3. Control of consumer exposure: Cosmetics, personal care products (PC 39)

Amount used, frequency and duration of use/exposure
Covers use up to 8.0 g/event
Frequency: 2 times/week
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to upper part of the body.
Dermal transfer factor: = 1

6.2.4. Control of consumer exposure: Disinfectant/disinfectant solutions for hemodialysis equipment (PC 35)

Amount used, frequency and duration of use/exposure
Covers use up to 5000 g/event
Frequency: 1 time/day

6.2.5. Control of consumer exposure: Water treatment chemicals (PC 37)

Amount used, frequency and duration of use/exposure
Covers use up to 1000 g/event
Frequency: 1 time/day
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to upper part of the body.

6.2.6. Control of consumer exposure: Water softeners - 2 (PC 36)

Amount used, frequency and duration of use/exposure
Frequency: 2 times/week
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to upper part of the body.
Dermal transfer factor: = 1

6.2.7. Control of consumer exposure: Washing and Cleaning Products (PC 35)

Amount used, frequency and duration of use/exposure
Covers use up to 1000 g/event
Frequency: 1 time/day
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to upper part of the body.

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Consumer Use (ERC 8a,8c,8f)

Not applicable

6.3.2. Consumer exposure: Water softeners -1 (PC 36)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	4.39E-4 mg/m ³ (External Tool: Consexpo 4.1)	< 0.01
Dermal, systemic, long-term	1.286 mg/kg bw/day (External Tool: Consexpo 4.1)	0.495
Combined routes, systemic, long-term		0.495

6.3.3. Consumer exposure: Cosmetics, personal care products (PC 39)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	2.98E-4 mg/m ³ (External Tool: Consexpo 4.1)	< 0.01
Dermal, systemic, long-term	2.286 mg/kg bw/day (External Tool: Consexpo 4.1)	0.879
Combined routes, systemic, long-term		0.879

6.3.4. Consumer exposure: Disinfectant/disincrustant solutions for hemodialysis equipment (PC 35)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.002 mg/m ³ (External Tool: Consexpo 4.1)	< 0.01
Combined routes, systemic, long-term		< 0.01

6.3.5. Consumer exposure: Water treatment chemicals (PC 37)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.009 mg/m ³ (External Tool: Consexpo 4.1)	< 0.01
Dermal, systemic, long-term	0.714 mg/kg bw/day (External Tool: Consexpo 4.1)	0.275
Combined routes, systemic, long-term		0.276

6.3.6. Consumer exposure: Water softeners - 2 (PC 36)

Route of exposure and type of effects	Exposure estimate	RCR
Dermal, systemic, long-term	1.009 mg/kg bw/day (External Tool: Consexpo 4.1)	0.388
Combined routes, systemic, long-term		0.388

6.3.7. Consumer exposure: Washing and Cleaning Products (PC 35)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long-term	0.002 mg/m ³ (External Tool: Consexpo 4.1)	< 0.01
Dermal, systemic, long-term	1.429 mg/kg bw/day (External Tool: Consexpo 4.1)	0.55
Combined routes, systemic, long-term		0.55